





15 m

30 m

50 m



Being able to sew



Being able to read



Being able to change a tire

	America	Ireland	Europe / Africa / Australia
<b>Model</b>	<b>S120-875W</b>	<b>S110-875W</b>	<b>S230-875W</b>
<b>Operation Voltage</b>	<b>120 Vac 60 Hz</b>	<b>110 Vac 50 Hz</b>	<b>230 Vac 50Hz</b>
<b>Lamp</b>			
Power	HID 875Watts	HID 875Watts	HID 875Watts
Type	Type-0 UV	Type-0 UV	Type-0 UV
Lumen	95 000 lm	95 000 lm	95 000 lm
Color Temperature	4000° K	4000° K	4000° K
Socket	E39	E40	E40
<b>Blower</b>			
Motor	500 Watts 120v 60Hz	500 Watts 120v 50Hz	500 Watts 240v 50Hz
<b>Case</b>			
Case	Fireproof Fibre Glass	Fireproof Fibre Glass	Fireproof Fibre Glass
Dimension	610mm (24")L x 466mm (18")H	610mm (24")L x 466mm (18")H	610mm (24")L x 466mm (18")H
Weight	33.5 Kg (74Lbs)	33.5 Kg (74Lbs)	33.5 Kg (74Lbs)
Color	Yellow	Yellow	Yellow
Other Colors	on demand	on demand	on demand
<b>Diffuser Tube</b>			
Material	Fireproof Coated Nylon	Fireproof Coated Nylon	Fireproof Coated Nylon
Model Height 2.5m (7')	2.24m (88")	2.24m (88")	2.24m (88")
Model Height 5m (15')	4.27m (14')	4.27m (14')	4.27m (14')
Diameter	400mm (17")	400mm (17")	400mm (17")
<b>Inspection / Approval</b>			
Electrical	as by CSA-SPE1000, NEC	CE	CE
Fabric	NFPA Method I-2004	M-1	M-1
Particles Penetration		IP44	IP44

© LUMINITE Int'l patent PTC33/99 by Guido Medici EIL Systems-Italy.

Available at:



For more information on how to rent yours today, call us at **1-855-563-7847** or visit our website at **www.lmtemperature.com**



INFLATABLE LIGHT TOWERS